

Tap offs 1-way DM 51... (F-type connector)

DM 51 1010



DM 51 1015



DM 51 1020



Type	DM 51 1010 Tap off, 1-way	DM 51 1015 Tap off, 1-way	DM 51 1020 Tap off, 1-way
Thru loss 5-2400 MHz	1.5-2.5 dB	1-2 dB	0.7-1.8 dB
Tap loss 5-2400 MHz	11 dB	15 dB	20 dB
Directional attenuation 5-40 MHz	32 dB	35 dB	40 dB
Directional attenuation 40-1000 MHz	25 dB	30 dB	32 dB
Directional attenuation 1000-2400 MHz	22 dB	25 dB	28 dB
Isolation 5-2400 MHz	-	-	-
Screening factor	>85 dB, Class A	>85 dB, Class A	>85 dB, Class A
DC-Bypass IN-OUT 1A, 30 V	yes	yes	yes
Dimensions	52x50x18mm	52x50x18mm	52x50x18mm
Packing unit	5 pieces, bag	5 pieces, bag	5 pieces, bag
Shipping package	200 pieces, 47 dm ³ , 12.8 kg	200 pieces, 47 dm ³ , 12.8 kg	200 pieces, 47 dm ³ , 12.8 kg

Notes

