

WISI DY 40

PROSWITCH SAT amplifier



Description

At a glance:

- 4 SAT polarizations in a compact form factor
- Gain from 30 dB
- Independent attenuation of 0...20 dB per input
- Selectable pre equalization to compensate frequency depending cable loss
- Simple extension up to 16 polarizations
- High screening efficiency according to Class A
- Colour-coded inputs and outputs

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 14. März 2017, 3:07 nachm.

Technical data

SAT	
Frequency range SAT	950...2150 MHz
Gain SAT	10...30 dB
Output level	115 dB μ V (3.order EN50083-3, 35 dB)
Attenuator SAT	
Attenuator SAT	0...20 dB
Slope	0,4,8,12 dB
Isolation trunk	40 dB typ.
Connectors	
F-socket	9 pcs.
DC supply voltage	F-socket
General data	
Operating voltage DC	12...18 V DC
Current consumption	200 mA
DC bypass	Yes
Screening factor	Class A, EN 50083-2
Dimensions (width x height x depth)	129 x 86 x 32 mm
Operating temperature range	-20...+50 °C
Weight	0,290 kg

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	170 x 160 x 50 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0,400 kg
Shipping unit	
Shipping unit	1 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	
Packaging volume shipping package	dm ³
Gross weight shipping unit	0,400 kg
EAN	4010056740276
Article number	73620
Customs tariff number	85437030