

WISI GNSTRX

Software option extension for IP streaming up to 128x in- and outputs



Description

The software option GNSTR + GNSTRX enables in the Chameleon up to 128 IP in- and outputs. The IP streaming interface can be used to feed an IPTV network or IP to edge device.

Scope of delivery

- After buying the software option you can download the entitlement file which includes the software option on www.wisiconnect.tv.

At a glance:

- High-density streamer with up to 128 IP SPTS/MPTS streams
- High-bitrate support for IP in- or outputs
- Support for PCR restamping and de-jittering
- SPTS CBR/VBR, MPTS CBR Support
- UDP/RTP/RTP+FEC Multicast/Unicast

Technical data

Streaming-In-/Output

IP-Inputs	20 or 128 pcs. (128 with GNSTRX Software option)
IP-Outputs	20 or 128 pcs. (128 with GNSTRX Software option)
IP-Compliance	ISO/IEC 13818
IP-Input bitrate	Max. 425 Mbit/s per IPTS, Max. 850 Mbit/s total
IP-Output bitrate	Max. 425 Mbit/s per IPTS, Max. 850 Mbit/s total
IP-Input protocol	UDP/RTP/RTP+FEC Unicast and Multicast, IGMP v2 and v3
IP-Output protocol	UDP/RTP/RTP+FEC Unicast and Multicast, IGMP v2 and v3
IP-TS-Input format	SPTS CBR/VBR, MPTS CBR
IP-TS-Output format	SPTS CBR/VBR, MPTS CBR
IP-FEC Inputs	20 or 128 pcs. (with GNSTREC Software option)
IP-FEC Outputs	32 pcs. (with GNSTREC Software option)

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	mm
Packaging volume sales unit	dm ³
Gross weight sales unit	kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	kg
EAN	4010056749026
Article number	74902
Customs tariff number	85437090