

Description


Local Area Network Cable

Cat. 6 F/UTP 4x2xAWG23/1 PVC




Data Sheet

LAN641



Ø	0,57	1,10			7,60
	(Cu)	(PE)	(Pet)	(Al/Pet)	(PVC)

Class CPR acc. to UE 305/2011 (DoP)



The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

EIA-TIA 568-B-2	ISO/IEC 11801	IEC 61156-5	EN 50173-1
EN 50288-5-1			

Fire-Resistance Rating

IEC 60332-1	EN50575
-------------	---------

Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)

IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T

IEEE 802.5; ATM

Power over Ethernet (PoE)/PoE+

Construction data

4 pairs with conductor of bare copper wires	(Cu)	Ø 0,57	mm
Insulation of solid Polyethylene	(PE)	Ø 1,10	mm
Polyester film spirally wrapped	(Pet)		

Composition

Twisted pairs, coloured by Standard TIA-568A

Drain wire of tinned copper	(CuSn)	Ø 0,40	mm
Cross separator in Polyethylene	(PE)		
External Aluminium/Polyester tape	(Al/Pet)	27 x 30/19	mm/µm
Outer sheath of Polyvinylchloride - white (PVC) - lead-free	(PVC)	Ø 7,60	mm

Printed each meter by blue ink-jet :

**CAVEL LAN 641 MADE IN ITALY CAT 6 F/UTP 4x2xAWG23 Euroclass Eca ISO-IEC 11801 EN50173
CEI-UNEL 36762 C-4 (U0 = 400V) gggaan - m**

(gggaan=batch number m=meter marking)

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

11/07/2017

Responsible

Alberto Scardovi

Description

Local Area Network Cable

Cat. 6 F/UTP 4x2xAWG23/1 PVC



Data Sheet

LAN641

Physical data

Weight of copper conductors	19,92	kg/km
Total weight of cable	52,56	kg/km
Minimum bending radius x1/n	35/70	mm
Maximum tensile strength during the installation	100	N
Minimum installation temperature	0 / +50	°C
Operating temperature	-20 / +60	°C

Electrical data

Characteristic impedance	100 MHz	100 ± 5	Ohm
Capacitance of Twisted Pair (@800Hz)		48	pF/m
Velocity Ratio		67 %	
DC Conductor Resistance		80	Ohm/km
Loop resistance		160	Ohm/km
Insulation resistance		> 5000	MOhm/km
Sheath Insulation Voltage (DC, 1 min)		1	kV
Coupling Attenuation		> 45	dB

Screening Attenuation (SA)

30 - 250 MHz	> 50 dB
250 - 1000 MHz	> 45 dB

Shield Transfer Impedance (Zt)

1 MHz	< 35 mOhm/m
10 MHz	< 41 mOhm/m
30 MHz	< 110 mOhm/m
100 MHz	< 150 mOhm/m

Transmission-Characteristic (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	SRL [dB]	NEXT [dB]	ACR [dB]	FEXT [dB]
1	1,80	25,00	100,00	98,20	90,00
10	5,40	25,00	80,00	74,60	70,00
20	7,70	25,00	70,00	62,30	60,00
31,2	9,60	25,00	65,00	55,40	53,00
62,5	13,70	25,00	60,00	46,30	50,00
100	17,40	25,00	60,00	42,60	48,00
155,5	21,90	25,00	55,00	33,10	46,00
200	25,00	20,00	55,00	30,00	44,00
250	28,10	20,00	50,00	21,90	40,00
300	30,80	20,00	45,00	14,20	

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

11/07/2017

Responsible

Alberto Scardovi