

WISI GNDTMOD

Software licence for two DVB-T outputs



Description

The Chameleon DVB-T modulators are enabled by the SW option GNDTMOD (dual DVB-T out). The DVB-T modulator supports both 2k and 8k mode, and all defined settings for modulation, FEC and Guard Interval. Complying to the DVB-T EN 300 744, the Chameleon DVB-T modulator gives professional DVB-T outputs for all types and sizes of cable networks.

At a glance:

- Up to 2 COFDM out in one Chameleon
- All modulation parameters
- Output frequency 40-860 MHz
- High output level
- High MER values
- Adjacent channels

Technical data

COFDM-Mode	2k, 8k switchable
Guard Interval	1/4, 1/8, 1/16, 1/32
FEC	1/2, 2/3, 3/4, 5/6, 7/8
MER	More than 38 dB, typical 40 dB dB
Modulation	QPSK, 16QAM, 64QAM
Output frequency	40-860 MHz MHz

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	mm
Packaging volume sales unit	dm ³
Gross weight sales unit	kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	kg
EAN	4010056717506
Article number	71750
Customs tariff number	