




Splitband amplifiers


VS 94



Splitband amplifier

Inputs	TERR	2x SAT
Frequency range	47-862 MHz	950-2150 MHz
Gain	-7 dB	25-32 dB
Equalization, switchable	-	0/6 dB
Output level, max. 2nd ord.	-	117 dB μ V
Output level, max. 3rd ord.	-	120 dB μ V
Noise figure	-	≤ 6 dB
Operating voltage	230 VAC	
Power consumption, max.	12,5 W	
LNC remote power supply	14 VDC	500 mA
Dimensions	177x122x40 mm	
EMC	CE, Class A	
Packing unit	1 piece	3.4dm ³ , 1.2 kg

VS 95



Splitband amplifier

Inputs	2x TERR +	SAT
Frequency range	47-862 MHz	950-2150 MHz
Gain	23-29 dB	25-32 dB
Equalization, switchable	0/5 dB	0/6 dB
Output level, max. 2nd ord.	106 dB μ V	117 dB μ V
Output level, max. 3rd ord.	118 dB μ V	120 dB μ V
Noise figure	≤ 6 dB	≤ 6 dB
Operating voltage	230 VAC	
Power consumption, max.	9 W	
Dimensions	177x122x40 mm	
EMC	CE, Class A	
Packing unit	1 piece	3.4 dm ³ , 1.2 kg

